



Security Management System

Model SBSRW

Barcode Slot Reader

Overview

The SBSRW Barcode Slot Reader combines innovative circuitry and optics to provide high 'first read' rates. The polycarbonate housing makes it ideal for indoor or outdoor applications.



FEATURES & BENEFITS

- Polycarbonate housing
- Visual indication provides one LED
- 3"-30" per second barcode scanning speed
- Bi-directional scanning
- Slot width is 0.050"
- Supports TTL/Open Collector interface format or Wiegand
- Optics resolution is 5 mil (high)/ 10 mil (low)
- Light source is 630nm visible/940 nm infrared

SPECIFICATIONS

- Dimensions: 2.4"W x 1.4"H x 4.6"L
- Power requirements: 5VDC
- Power consumption: 145mA typical 245 max at 5VDC
- Operating temperature: -40F to 170F
- Weight: 7 oz.
- Cable distance: 50' with 18AWG 6 conductor stranded with overall shield to reader interface

ORDERING INFORMATION

SBSRW - Barcode Slot Reader TTL/Open Collector

SBSRW-WIEG - Barcode Slot Reader Wiegand interface format

SBSRW-TP - Barcode Slot Reader Thermal Paper

SBSRW-V - Barcode Slot Reader- Visual

SBSRW-OP - Barcode Slot Reader- Optical



Schlage

Electronic Security
575 Birch Street
Forestville, CT 06010 USA
Tel 860-584-9158/866-322-1237
Fax 860-584-2136/866-322-1233
Tel 800-950-4573 (Toll Free Canada)
www.schlage.com